



STEAM GENERATOR EVO BLU

Body material
Varnished steel

Boiler material
Stainless steel AISI 304

(with interchangeable heating element)

Boiler volume
Mod. Det, Water, 24/7: 1,5 L | Mod. Base 4 L

Water tank **Water capacity**
Mod. Det, Water, 24/7: 3 L Mod. Base: 3 L

Detergent tank
Mod. Det: 1 L

Maximum output
2,45 kW

Boiler output
2,4 kW

Steam production
64 g/min | 3,8 Kg/h

Power supply
1 ~ 230V - 50/60 Hz

Steam T°
165° C

Detergent T°
90° C - 160° C (Mod. Det)

Power cord
5 m

Weight
16 Kg | Mod. Base: 14 Kg

Packaging
53x40x52 cm



Optional trolleys:



APPLICATIONS



Single-phase steam generator for usage in the professional sector, with a varnished steel body, unlimited steam autonomy thanks to the automatic refilling system with an internal water tank (electromechanical water level control system inside the boiler – True Temp™). Possibility to inject detergent (or hot water) together with steam. The steam generator's front panel is equipped with an electric console with commands for a timer, a thermometer and a pressure gauge; the digital display will advise the user about the necessity to proceed with the boiler maintenance.



TOOLS



JULY 6 BAR
Steam 165°C



Mod. Dublo



Mod. Tulipano

PROFESSIONAL IRONS



System tested by the
University of Verona

STEAM MOP
Steam 165°C

