



STEAM GENERATOR

STEAM BOX VAC MINI

Body material

Stainless steel AISI 304 (BA)

Boiler material

Stainless steel AISI 304

(with interchangeable heating element)

Boiler volume

5 L

Tanks

Water: **7,5 L** | Det: **7,5 L**

Maximum output

3,75 kW

Boiler output

3,6 kW

Steam production

97 g/min | **5,9 Kg/h**

Power supply

1~ 230V - 50/60 Hz | **3~ 400V - 50/60 Hz**

Steam T°

6 bar: **165° C** | 10 bar: **183° C**

Detergent T°

90° C - 160° C

Vacuum output

1,2 kW

Vacuum drum capacity

Plastic: **5,5 L** | Stainless steel: **7,5 L**

Air flow

200 m3/h

Depression

2200 mm

Power cord


8 m

Weight

35 Kg

Packaging

63x45x75 cm



without vacuum



10
bar

6
bar



APPLICATIONS



Three-phase or single-phase steam generator for usage in the professional sector, with a stainless-steel body (watertight protection IPX5), **unlimited steam autonomy** thanks to the automatic refilling system with either an internal water tank (electromechanical water level control system inside the boiler – True Temp™) or directly with a water mains connection. **Possibility to inject detergent (or hot water as optional) together with steam.**

Equipped with a wet&dry vacuum cleaner with float.

The steam generator's front panel is **equipped with an electric console with commands for a timer, a thermometer and a pressure gauge**; the digital display will advise the user about the necessity to proceed with the boiler maintenance.



TOOLS



GEYSER 1 10 BAR
Steam 183°C



RADAMES 10bar
Steam/vacuum 183°C



RADAMES 6 BAR
Steam/vacuum 165°C



JULY 10 BAR
Steam 183° C



JULY 6 BAR
Steam 165° C



STAR 6 BAR
Steam/vacuum 165°C



System tested by the
University of Verona

STEAM MOP
Steam 165°C

