



STEAM GENERATOR

STEAM BOX VAC INDUSTRIAL

Body material

Stainless steel AISI 304 (BA)

Boiler material

Stainless steel AISI 304

(with interchangeable heating element)

Boiler volume

11 L - 12,5 L

Tanks

Water: **20 L** | Det: **20 L**

Maximum output

11,1 - 15,8 - 22,15 kW

Boiler output

10 - 14,4 - 20,75 kW

Steam production

291 - 388 - 564 g/min

17,5 - 23 - 33,8 Kg/h

Power supply

3~ 400V - 50/60 Hz

Steam T°

183° C

Detergent T°

90° C - 160° C

Vacuum output

1 kW

Vacuum drum capacity

7,5 L

Air flow

200 m3/h

Depression

2200 mm

Power cord

8 m

Weight


113 Kg

Packaging


115x65x125 cm



induction turbine



APPLICATIONS



Three-phase steam generator for usage in the industrial sector, with a stainless-steel body (watertight protection IPX5), **unlimited steam autonomy** thanks to the automatic refilling system with either an internal water tank (electromechanical water level control system inside the boiler – True Temp™) or directly with a water mains connection. **Possibility to inject detergent or hot water together with steam. Equipped with an integrated wet&dry vacuum cleaner with an induction turbine.** The steam generator's front panel is **equipped with an electric console with commands for a timer, a thermometer and a pressure gauge**; the digital display will advise the user about the necessity to proceed with the boiler maintenance.



TOOLS



GEYSER 10 BAR
Steam 183°C



RADAMES 10 BAR
Steam&vacuum 183°C

